

Pipette Tips Table of Contents

58	Pipette Tips
60	Optifit Tips
62	SafetySpace Filter Tips
63	Low Retention Tips
64	Packaging Options
66	Ordering Information

Pipette Tips The Perfect Match for Your Pipette



Optiload for a tight fit and equal sealing on every channel's tip cone.



The factory in Kajaani, Finland.

	💐 sartorius
	Certificate of Quality
Θ	Magin Tao Tao II - Milar Gal Randar MEDI Lat Randar Hendel
	ha gendezi disorikat daren har hari kari daribektenat in anzarlaren artik 80 orangenter personak partikan na. 1970a Deri da Ma Pantik, partan paran arater pensaken situat in dia peninti
The angle Adds of the fire participing	d is for Disson, Mysear and excellences from and is second by an exclusioning interactive product to 1 peaks from the constructioning tech and is extent or the product radie of the
night this patients for 17 million	where is a second to TM application to control former to matching to control to the second to the s
White with \$10 the art	ng and dear is an addressed waters of game value and respectively applied in applied and the same manufacture of functioners, and the dearbing importance of waters from adults take often the attitutes of Wilson adults is the assoc with the dearbine local
-1.10710 Statutes	
The loss and particular	to and more is an updresser related of parts rater and memory applies to respect today the memory of the borneous pression of the day dependent of parts of the
The spanning parties of	is not show it is indicated where if you water any spectra spectra to constru- tedar we reason with formatic spectra to starting spectra if you have been been up on the spectra of the spectra of the spectra of the spectra of the spectra of the spectra of the sp
The loss and particular	a per lane is a splitting relation of part with any spectra splitting is speci- tic per lane is a splitting relation of the splitting spectra splitting is specific top of the splitting splitting splitting relation is a splitting splitting splitting splitting splitting splitting splitting is a splitting sp

Lot-specific purity certificate

In liquid handling, accurate pipetting results are not dependent on the pipette or the tip alone, but a combination of these and the comfort of the user. Our non-filter Optifit Tips and SafetySpace Filter Tips are designed and manufactured to perfectly fit for our pipettes, enabling maximal accuracy, precision and ergonomics. Moreover, wellmatching tips protect the pipette tip cone from wear and tear. The unique Optiload mechanism of our pipettes allows tip attachment and loading with reduced force, but with complete sealing, which is vital to get accurate results.

Sartorius tips correspond with the colour-coding of Sartorius pipettes, to allow easy matching of corresponding volumes.

Premium Quality and Purity

Manufacturing the tips in our own production facility allows us to maintain the highest quality and purity standards, by selecting the best plastic materials and controlling the manufacturing process from beginning to end. Our quality management system follows not only ISO 9001 and ISO 14001, but also ISO 13485. Tip production also abides by the ISO 14644-1 standard, in order to fulfil ISO Class 8 cleanroom conditions for secured tip purity.

Contamination Free Tips

To avoid contamination through human contact, we have automated the entire tip manufacturing process. Pure virgin polypropylene (PP) plastic is automatically fed from silos into moulding machines. Moulding machines and robots located in isolated clean cells, load the tips automatically into tip trays and packaging. HEPA filters and higher air pressure are applied for purity within the cell. All Sartorius Single Tray tip racks, Single Refill Packs and FlexiBulk® packs are individually and automatically packed in air-tight plastic, in order to rule out any danger of contamination.

Additionally, our highly experienced and trained personnel are equipped with specially designed coveralls, masks, hair nets and gloves, in order to further diminish risks of contamination.

An independent laboratory checks every FlexiBulk[®], Single Tray and Refill Pack tip lot for RNase, DNase and endotoxins. Lot-specific purity certificates can be downloaded from www.sartorius.com (select from the navigation bars: -> Liquid Handling -> Tip Purity Certificates).









Definitions:

A deoxyribonuclease (DNase) is any enzyme that catalyzes the degradation of DNA. The absence of DNase is tested by using fluorometric assay. The detection level of the assay is $6,25^*$ 10-5 U/µl when DNase I is used as a standard.
Ribonuclease (RNase) is an enzyme that catalyzes the degradation of RNA into smaller components and can be generally found from organisms. The absence of RNase is tested by using fluorometric assay. The detection level of the assay is 3,125* 10-9 U/µl, when RNase A is used as a standard.
Endotoxins are lipopolysaccharides found in the Gram- negative bacteria and can cause several serious health effects in humans and animals. Limulus Amebocyte Lysate (LAL) Gel Clot method is used to detect the presence of endotoxins on the pipette tips. The detection level of the LAL assay is 0,005 IU/ml (EU/ml).
The destruction of all microbial life, including bacterial endospores. Can be accomplished e.g. using steam, heating, chemicals, or radiation. We use e-beam irradiation.

Features and Benefits

Best Fit – Highest Possible Accuracy

- Perfect fitting and sealing with Sartorius pipettes secure the highest possible accuracy and precision
- Compatible with Optiload feature in Sartorius Picus® NxT, Picus®, Tacta®, eLINE®, mLINE® and Proline® Plus pipettes enabling ergonomic and light tip attachment and ejection
- Colour-coding of tip trays allows easy matching with a corresponding colour-coded

Sartorius pipette

 Compatible with most other pipette makes

Premium Quality and Purity:

- Strict quality standards, ISO 9001 and ISO 13485, are followed from R&D to production and delivery
- Manufactured in ISO 8 classified clean room conditions
- Manufacturing process free of DNase, RNase and endotoxins: Single Trays, Refill Packs and FlexiBulk[®] packs certified pure by

lot number

- Pre-sterilised tips are e-beam irradiated
- All tip packages, including individual racks, are lot numbered for full traceability
- The highest quality virgin polypropylene used as raw material

□ Tip Selection Guide per Application

Тір Туре	Optifit Tips	5	SafetySpace Filter Tips	Low Retention Tips	
Purity	Standard	Free of DNase, RNase & endotoxins	Pre-sterilized & free of DNase, RNase and endotoxins	Pre-sterilized & free of DNase, RNase and endotoxins	
Regular pipetting applications	√				
Applications where prevention of cross-contamination is vital		✓	✓	\checkmark	
Pipetting liquids with low surface tension (e.g. detergents, solvents)					✓

Optifit Tips

Standard Tips for Various Needs



Sartorius Optifit tips are an excellent choice for various laboratories and pipetting tasks with their wide range of packaging and purity options. The Optifit tips are packed in single tray racks, refill towers, single refill packs, and bulk packages. Optifit tips are available DNase, RNase and endotoxin free, as well as e-beam pre-sterilized. The Single Tray tip racks are ideal for easy tip loading and for contamination-free pipetting. In order to reuse the empty tip racks and to create less waste, you may fill the empty racks with Refill tips, either using the refill tower or purity certified refill pack tips. The FlexiBulk[®] pack is the choice, if you need a cost-effective, yet puritycertified solution, in bulk tip format.

Available Packaging Options

- Single tray rack
- Refill tower
- Refill pack
- FlexiBulk[®] pack
- Bulk in a box

See details on packaging options on pages 64 and 65.

Features and Benefits

- Standard non-filter tips made to Sartorius quality standards
- Low Retention Tip range also available for liquids with low surface tension
- Perfect fitting and sealing with Sartorius Picus[®] NxT, Picus[®], Tacta[®], eLINE[®], mLINE[®], Proline[®] Plus, and Proline[®] pipettes
- Wide tip volume range from 10 μl to 10 ml

- Wide selection of packaging and purity options
- Available as DNase, RNase and endotoxin-free
- e-beam pre-sterilized packaging options available
- Full traceability
- Colour-coded trays to match with corresponding Sartorius pipettes
- Fully autoclavable at 121°C , at 1 bar, for 20 minutes

SafetySpace Filter Tips

Protect Valuable Samples



SafetySpace Filter Tips , made of virgin polypropylene, feature filter barriers that effectively capture solid and liquid aerosol particles. The filter is made of polyethylene without self-sealing additives to avoid any interference with the sample and results. The filter protects the sample against contamination. In addition, it protects the pipette and prolongs the maintenance interval of the pipette.

The SafetySpace Filter Tips are Ideal for:

- molecular biology
- microbiology
- cell culture applications
- radioactive work

The unique feature with SafetySpace Filter Tips is the additional space left between the sample and the filter that conventional filter tips do not have. This extra space prevents the liquid from touching, and permeating, the filter and thus guarantees the pipetting accuracy. Any liquid types and pipetting techniques can be applied without the risk of the liquid permeating the filter.

The Extra Space is Particularly Useful in the Following Applications:

- pipetting foaming liquids such as buffers and proteins
- pipetting solvents
- multiple dispensing functions of electronic pipettes
- reverse pipetting

Available Packaging Options

- Single Tray Rack

Features and Benefits

- Filter minimizes the risk of aerosol contamination
- Large empty volume between the sample and filter prevents liquid from contacting the filter
- Covers tip volumes from 10 μl to 1200 μl
- Certified free of DNase, RNase and endotoxins
- e-beam pre-sterilized
- Full traceability
- Colour-coded trays indicate the matching colour-coded Sartorius pipette

Low Retention Tips

Ensure Optimal Sample Recovery



The four tips on the right are low retention tips, providing maximum sample recovery.

Pipetting liquids that contain detergents can be problematic when using standard pipette tips. Some liquid residue often remains in the tip due to differences in surface energies between the plastic pipette tip and the sample. The residue causes imprecision in pipetting and loss of valuable samples or reagents.

We use an advanced technology to manufacture Low Retention Tips that have an extremely even and durable hydrophobic surface. Unlike some other hydrophobic tips on the market, our low retention tips do not contain any leachables that might risk your sample. Low Retention Tips maximize the sample recovery, when handling detergent containing or other liquids with low surface tension. Better reproducibility in pipetting is especially beneficial in sensitive molecular biology applications, where reagents often contain detergents, for example in:

- PCR, real-time PCR
- Cloning, sequencing and other DNA & RNA techniques
- SDS-PAGE and other protein analysis methods
- Protein purification techniques



Packaging options for Low Retention tips.



Available Packaging Options

- Single Tray Rack
- Refill Tower

Features and Benefits

- Extremely hydrophobic tips surface
- Maximum sample recovery for fluids with low surface tension
- Durable, high chemical resistance, no leachables
- Covers tip volumes from 10 μl to 1200 μl
- Filter (SafetySpace) and non-filter (Optifit) tip options are available
- DNase, RNase and endotoxin-free

- packaging options available
- e-beam pre-sterilized packaging options available
- Full traceability
- Colour-coded trays indicate the matching colour-coded Sartorius pipette
- Non-filter tips are fully autoclavable at 121°C, at 1 bar, for 20 minutes

Low	Retention T	ips	Pip	oette	Tip



Packaging Options



Single Tray Racks





Refill Towers

Racked Tips

Single Tray Rack

- 96 tips in convenient and reusable tray racks (sales unit contains 10 tray racks, total 960 tips)
- Certified free of DNase, RNase and endotoxins
- e-beam pre-sterilized option available
- Lot-specific purity certificates can be downloaded from www.sartorius.com
- Informative rack labelling: volume, product number, lot number improves tip identification and traceability

- Air-tight plastic wrapping around the rack secures purity during transport and storage (wrapping is regular waste)
- Tip trays are colour-coded to indicate the matching, colourcoded Sartorius pipette
- Covers a large range of tip volumes from 10 μl to 5 ml
- Fully autoclavable at 121°C , at 1 bar, for 20 minutes
- Tray racks can be easily reloaded with Refill tips
- Racks, trays and tips are 100% recyclable polypropylene (PP)

🗌 Refill Tips

Refill Tower

- Space-saving with 10x96 tips in one tower
- Tip trays are compatible with Single Tray racks for convenient use
- Trays are colour-coded to indicate the matching, colour-coded Sartorius pipette
- Covers the most widely used tip sizes: 10 μl, 200 μl and 350 μl
- Trays and tips are fully autoclavable at 121°C, at 1 bar, for 20 minutes
- 100% recyclable cardboard packaging, and plastic (PP) trays and tips



Single refill packs





FlexiBulk®

Entre Entre



Bulk in a box

Single Refill Packs

- 10, 15 or 20 trays of 96 tip trays, depending on tip volume
- Certified free of DNase, RNase and endotoxins
- e-beam pre-sterilized option available
- Lot-specific purity certificates can be downloaded from www. sartorius.com
- Individually packed air-tight tip trays for maximum purity with less packaging material compared to racked tips
- Tip trays are compatible with Single Tray racks for convenient use

Bulk Tips

FlexiBulk®

- Tips made to the Sartorius quality standard in economical packaging
- Packed orderly in compact resealable plastic packages (480 or 960 pcs depending on tip volume)
- Covers a large range of tip volumes from 200 μl to 1200 μl

- Informative rack labelling: volume, product number, lot number improves tip identification and traceability
- Tip trays are colour-coded to indicate the matching, colourcoded Sartorius pipette
- Covers a large range of tip volumes from 10 μl to 1200 μl
- Trays and tips are fully autoclavable at 121°C, at 1 bar, for 20 minutes
- 100% recyclable trays and tips (PP). Container lid is regular waste.
- Certified free of DNase, RNase and endotoxins
- Lot-specific purity certificates can be downloaded from www. sartorius.com
- Tips are fully autoclavable at 121°C, at 1 bar, for 20 minutes
- 100% recyclable tips (PP) and package (PET)

Bulk in a Box

- Tips made to the Sartorius quality standard in economical packaging
- Packed in re-sealable bags in cardboard boxes (100, 250 or 1000 pcs depending on tip volume)
- Covers tip volumes 10 μl, 5 ml and 10 ml
- Tips are fully autoclavable at 121°C, at 1 bar, for 20 minutes
- 100% recyclable tips and package

Ordering Information

Optifit Tips

Volume Range	Length	Packaging	Low Retention	Purity Level		Tips/ Unit	Order Code
				Free of RNase, DNase, endotoxins	Pre- sterilised		
0,1-10 μΙ	31,5 mm	Single Tray Single Tray Single Tray Refill Tower Refill Tower Refill Pack Bulk in Box	•	•	•	10 x 96 10 x 96 10 x 96 10 x 96 10 x 96 20 x 96 1000	790010 LH-L790010 790011 790012 LH-L790012 790013 790014
0,1-10 μl Extended	46 mm	Single Tray Single Tray		•	•	10×96 10×96	783210 783211
ο 0,5-200 μl	51 mm	Single Tray Single Tray Single Tray Refill Tower Refill Tower Refill Pack FlexiBulk [®]	•	•	•	10 x 96 10 x 96 10 x 96 10 x 96 10 x 96 15 x 96 960	790200 LH-L790200 790201 790202 LH-L790202 790203 LH-B790204
 5-350 μl 	54 mm	Single Tray Single Tray Single Tray Refill Tower Refill Tower Refill Pack FlexiBulk [®]	•	•	•	10 x 96 10 x 96 10 x 96 10 x 96 10 x 96 15 x 96 960	790350 LH-L790350 790351 790352 LH-L790352 790353 LH-B790354
 10-1000 μl 	71,5 mm	Single Tray Single Tray Single Tray Refill Pack Refill Pack FlexiBulk®	•	• • • •	•	10 x 96 10 x 96 10 x 96 10 x 96 10 x 96 480	791000 LH-L791000 791001 791002 791003 LH-B791004

For your guidance the tips are illustrated in the actual size.

Empty Tip Boxes for Refill System (Tips and Trays are Not Included)

Item	Tip Type (Non-filter Tips)	Racks/Unit	Order Code
Empty Tip Box for Refill System	10, 200, 350 μl	10	790910
Empty Tip Box for Refill System	1000, 1200 μl	10	790920

Volum	ie Range		Length	Packaging	Low Retention	Purity Level		Tips/ Unit	Order Code
						Free of RNase, DNase, endotoxins	Pre- sterilised		
• 1	0-1000 μl	Wide bore tip	68,5 mm	Single Tray Single Tray FlexiBulk®		•	•	10 x 96 10 x 96 480	791020 791021 LH-B791024
• 5	50-1200 μl		71,5 mm	Single Tray Single Tray Single Tray Refill Pack Refill Pack FlexiBulk [®]	•	• • •	•	10 x 96 10 x 96 10 x 96 10 x 96 10 x 96 480	791200 LH-L791200 791201 791202 791203 LH-B791204
• 5	i0-1200 μl	Extended	90 mm	Single Tray Single Tray Single Tray Refill Pack Refill Pack	•	• • •	•	10 x 96 10 x 96 10 x 96 10 x 96 10 x 96	791210 LH-L791210 791211 791212 791213
• 1 μ	00-5000 II		150 mm	Single Tray Single Tray Bulk in Box Bulk in Box		•	•	50 50 100 1000	780304 780305 780300 780308
					-				
• 1	-10 ml		155 mm	Bulk in Box				250	LH-780316

Note: The ordering information for 10 ml tip for Midi Plus can be found on page 69.

NOTE! Tip compatibility with pipettes are shown in the Tip Selection Guides at Electronic Pipettes, page 25, and Mechanical Pipettes, pages 46 - 47.

SafetySpace Filter Tips

Volume Range		Length	Packaging Low Retention		Purity Level		Tips/ Unit	Order Code
					Free of RNase, DNase, endotoxins	Pre- sterilised		
• 0,	1-10 μl	31,5 mm	Single Tray Single Tray	•	•	•	10 x 96 10 x 96	790011F LH-LF790011
0,	5-20 μl	51 mm	Single Tray Single Tray	•	•	•	10 x 96 10 x 96	790021F LH-LF790021
<u> </u>	-120 μl	51 mm	Single Tray Single Tray	•	•	•	10 x 96 10 x 96	790101F LH-LF790101
<u> </u>	-200 μl	52,5 mm	Single Tray Single Tray	•	•	•	10 x 96 10 x 96	790201F LH-LF790201
- 5-	-300 μl	52,5 mm	Single Tray Single Tray	•	•	•	10 x 96 10 x 96	790301F LH-LF790301
50	0-1000 μl	78 mm	Single Tray Single Tray	•	•	•	10 x 96 10 x 96	791001F LH-LF791001
• 50	D-1200 μl	90 mm	Single Tray Single Tray	•	•	•	10 x 96 10 x 96	791211F LH-LF791211

For your guidance the tips are illustrated in the actual size. Filter tips are not recommended to be used simultaneously with Safe-Cone Filters

Volume Range	Length	Packaging	Low Retention	Purity Level		Tips/ Unit	Order Code
				Free of RNase, DNase, endotoxins	Pre- sterilised		
0,1-10 μl Extended	46 mm	Single Tray		•	•	10x96	783201

NOTE! Tip compatibility with pipettes are shown in Tip Selection Guides at Electronic Pipettes, page 25, and Mechanical Pipettes, pages 46 - 47.